

Monofilament polyester 22/100 braided sleeving



Standards*

- Compliant with directive RoHS 2011/65/CE
- NF EN 60684-1 (10-2003)
- NF EN 60684-2 (07-2012)
- NF EN 60684-3 sheets 340 to 342 (4-2003)
- On request : UL94 V0 or UL94 VW1

Colours and packagings

- Manufactured diameters : 3 to 60 mm
- Standard colour : black or grey

Characteristics

- Temperature class : F
- Continuous working temperature : from -50°C to +155°C. Peaks at +180°C
- Halogen free
- Flammability : self-extinguishing
- Good mechanical resistance
- Excellent resistance to abrasion
- Good resistance to solvent
- Non watertight
- Very flexible
- Expansion ratio : 1 : 2
- Use : hot cutting to avoid fraying

- Standard packaging : rolls
 - diameter 3 : 200 m
 - diameter 4 to 12 mm : 100 m
 - diameter 15 to 30 mm : 50 m
 - diameter 40 to 60 mm : 25 m

Applications



Inner nominal diameter (mm)	3	4	5	6	8	10	12	15	20	25	30	40	50	60
Inner maximal diameter (mm)	6	8.5	10.5	12	15	19	22	25	30	38	49	64	70	84
Minimum diameter of use (mm)	2	2.5	3	4	5	6.5	8	10	14	16	21	25	32	42
Maximum diameter of use (mm)	5	7	9	10	13	17	19	22	27	35	45	60	65	75

*Our products pass all or parts of requirements for the above-mentioned standards. The technical information written on our datasheets correspond to the most recent knowledges we have on those products, but the user is not exempted to verify the performances in the real particular context of application.

