

Heat-shrinkable tubes



Applications



Selection guide

References	Ratios	Designations
Polyolefin and PVC – Thin wall tubings		
TER-102	2:1	105°C, Heat - Shrinkable tubing in PVC, shiny surface
TER-103	2:1	125°C, Heat - Shrinkable tubing in polyolefin, UL94 VW-1
TER-104	2:1	125°C, Heat - Shrinkable tubing in polyolefin, UL94 VW-1 in MINIBOX
TER-105	2:1	135°C, Heat - Shrinkable tubing in polyolefin, UL 224 VW-1
TER-106	3:1	125°C, Heat - Shrinkable tubing in polyolefin, UL224 VW-1
Polyolefin – Dual wall tubings (with adhesive)		
TER-202	3:1	125°C, Heat - Shrinkable tubing in polyolefin with adhesive
TER-203	4:1	125°C, Heat - Shrinkable tubing in polyolefin with adhesive
Other thin wall and special tubings		
TER-301	2:1	175°C, Heat - Shrinkable tubing in KYNAR, UL224 VW-1
TER-302	2:1	190°C, Heat - Shrinkable tubing in KYNAR, UL224 VW-1
TER-303	2:1	200°C, Heat - Shrinkable tubing in fluoroelastomer VITON, UL224 VW-1
TER-304	2:1/4:1	260°C, Heat - Shrinkable tubing in PTFE
Medium and heavy wall tubings		
TER-401	4:1	125°C, Medium wall heat - shrinkable tubing
TER-402	4:1	125°C, Heavy wall heat - shrinkable tubing
TER-403	4:1	125°C, Medium wall heat - shrinkable tubing with adhesive
TER-404	4:1	125°C, Heavy wall heat - shrinkable tubing with adhesive
TER-405	6:1	125°C, Heat - shrinkable tubing with adhesive
Medium voltage products		
TER-501	2:1	105°C, Heat Shrinkable tubing for medium voltage BUS-BAR of medium thickness
TER-502	2:1	105°C, Heat Shrinkable tubing for medium voltage BUS-BAR of high thickness
Moulded parts		
TER-601	3:1	100°C, Adhesive-lined heat shrinkable end cap

